



### #2352 Silver Plated Copper Tubular Braid (Mil Spec QQ-B-575 & A-A-59569)

Woven silver plated copper shielded braid manufactured round per Mil Spec QQ-B-575 & A-A-59569.

- Individual wire strands have 40 micro-inches of silver plating over copper meeting ASTM B298.
- Use silver plating, in lieu of tin plating, when the shielding is to be subjected to temperatures exceeding 150° C or if special corrosion resistance is required.
- For military and commercial applications where maximum shielding is required.
- Also useful against mechanical abrasion and stresses for cables and as grounding cable.

Daburn Part Number	Nom. ID Rounded	QQ-B-575 Mil Spec	A-A-59569 Mil Spec	Construction	AWG Equivalent	Nominal CMA	Nom. Amps
2352-1/32	1/32"	QQB575R36S0031	AA59569R36S0031	24-1-36	22	600	7
2352-1/16	1/16"	QQB575R36S0062	AA59569R36S0062	24-2-36	19	1200	11
2352-1/16A	1/16"	QQB575R32S0062	AA59569R32S0062	16-1-32	20	1024	9
2352-1/16B	1/16"	QQB575R34S0062	AA59569R34S0062	16-2-34	19	1270	11
2352-5/64	5/64"	QQB575R36S0078	AA59569R36S0078	24-3-36	18	1800	16
2352-7/64	7/64"	QQB575R36S0109	AA59569R36S0109	24-4-36	16	2400	19
2352-7/64A	7/64"	QQB575R32S0109	AA59569R32S0109	16-2-32	17	2048	18
2352-7/64B	7/64"	QQB575R34S0109	AA59569R34S0109	16-4-34	16	2541	19
2352-1/8	1/8"	QQB575R36S0125	AA59569R36S0125	24-5-36	15	3000	25
2352-1/8A	1/8"	QQB575R32S0125	AA59569R32S0125	24-2-32	15	3072	25
2352-1/8B	1/8"	QQB575R34S0125	AA59569R34S0125	24-3-34	16	2858	19
2352-9/64	9/64"			24-4-34	15	3811	26
2352-5/32	5/32"	QQB575R36S0156	AA59569R36S0156	24-10-36	12	6000	40
2352-11/64	11/64"	QQB575R36S0171	AA59569R36S0171	24-7-36	14	4200	32
2352-11/64A	11/64"	QQB575R32S0171	AA59569R32S0171	24-3-32	14	4608	32
2352-11/64B	11/64"	QQB575R34S0171	AA59569R34S0171	24-5-34	14	4764	32
2352-3/16A	3/16"			24-6-34	13	5717	38
2352-13/64	13/64"	QQB575R36S0203	AA59569R36S0203	24-13-36	11	7800	46
2352-13/64A	13/64"	QQB575R32S0203	AA59569R32S0203	24-5-32	11	7680	46
2352-13/64B	13/64"	QQB575R34S0203	AA59569R34S0203	24-8-34	11	7622	46
2352-1/4	1/4"	QQB575R36S0250	AA59569R36S0250	24-16-36	10	9600	53
2352-1/4A	1/4"			24-7-34	12	6670	41
2352-9/32	9/32"	QQB575R30S0281	AA59569R30S0281	30-5-24	9	12000	60
2352-3/8	3/8"	QQB575R36S0375	AA59569R36S0375	48-8-36	10	9600	53
2352-3/8A	3/8"	QQB575R30S0375	AA59569R30S0375	30-7-24	8	16800	75
2352-3/8B	3/8"	QQB575R32S0375	AA59569R32S0375	48-3-32	11	9216	46
2352-3/8C	3/8"			24-8-34	11	7622	46
2352-3/8D	3/8"	QQB575R34S0375	AA59569R34S0375	48-5-34	10	9528	53
2352-7/16	7/16"	QQB575R30S0437	AA59569R30S0437	30-10-24	6	24000	90
2352-1/2	1/2"	QQB575R36S0500	AA59569R36S0500	48-11-36	9	13200	62
2352-1/2A	1/2"	QQB575R30S0500	AA59569R30S0500	24-15-30	5	36000	120
2352-1/2B	1/2"	QQB575R32S0500	AA59569R32S0500	48-4-32	9	12288	62
2352-1/2C	1/2"	QQB575R34S0500	AA59569R34S0500	48-7-34	9	13339	62
2352-9/16A	9/16"	QQB575R30S0562	AA59569R30S0562	48-10-30	3	48000	145
2352-5/8	5/8"			48-8-34	8	15245	64
2352-21/32	21/32"	QQB575R30S0656	AA59569R30S0656	48-16-30	1	76800	190
2352-11/16	11/16"			48-10-34	7	19056	81
2352-25/32	25/32"	QQB575R36S0781	AA59569R36S0781	48-18-36	7	21600	88
2352-25/32A	25/32"	QQB575R32S0781	AA59569R32S0781	48-7-32	7	21504	88
2352-25/32B	25/32"	QQB575R34S0781	AA59569R34S0781	48-11-34	7	20962	85
2352-13/16A	13/16"			48-12-34	7	22867	90
2352-7/8	7/8"	QQB575R30S0875	AA59569R30S0875	48-7-30	5	33600	100
2352-7/8A	7/8"			48-19-36	7	22800	93
2352-1"	1"	QQB575R30S1000	AA59569R30S1000	48-8-30	4	38400	120
2352-1 1/8	1 1/8"	QQB575R30S1125	AA59569R30S1125	48-9-30	4	43200	130
2352-1 1/4	1 1/4"	QQB575R30S1250	AA59569R30S1250	48-10-30	3	48000	145
2352-1 3/8	1 3/8"	QQB575R30S1375	AA59569R30S1375	48-11-30	3	52800	145
2352-1 1/2	1 1/2"	QQB575R30S1500	AA59569R30S1500	48-12-30	3	57600	145
2352-2"	2"	QQB575R30S2000	AA59569R30S2000	48-14-30	2	67200	180