



Daburn Electronics & Cable
44 Richboynton Road
Dover, NJ 07801

#DES100 Expandable PET Braided Sleeving – General Purpose

Daburn Expandable PET (polyethylene terephthalate) Sleeving is ideal for general all-purpose wire management and bundling in industrial, commercial and home environments.

Description: Expandable monofilament PET braided sleeving that easily expands for ease of installation and then pulls tight for snug fit.

- High expansion ratio
- Excellent mechanical abrasion resistance
- Cut resistant
- Resist gasoline and all other common automotive fluids
- UL Listed

Operating Temperature: -70°C to +125°C

Material should be cut with a hot knife.

Daburn Cat. No.	Nom. I.D.	Expansion Range	Wall Thickness	Spool Size
DES100-1/8	1/8"	3/32" – 1/4"	.025"	1,000 feet
DES100-1/4	1/4"	1/8" – 3/8"	.025"	1,000 feet
DES100-1/4-3	1/4" (3 End)	1/8" – 3/8"	.025"	1,000 feet
DES100-3/8	3/8"	1/4" – 5/8"	.025"	500 feet
DES100-1/2	1/2"	3/8" – 3/4"	.025"	500 feet
DES100-3/4	3/4"	1/2" – 1-1/4"	.025"	250 feet
DES100-1"	1"	5/8" – 1-1/2"	.025"	250 feet
DES100-1 1/4"	1 1/4"	7/8" – 1-3/4"	.025"	250 feet
DES100-1 1/2"	1 1/2"	1" – 2"	.025"	250 feet
DES100-1 3/4"	1 3/4"	1 1/4" – 2-3/4"	.025"	250 feet
DES100-2"	2"	1-1/2" – 3-1/2"	.025"	250 feet
DES100-2 1/2"	2 1/2"	1-3/4" – 3-3/4"	.025"	100 feet
DES100-3"	3"	1 7/8" – 4-1/2"	.025"	100 feet

Standard Put-Ups: Sold in Standard Spool Quantities Only.

Colors Available: Black, Clear/Natural, Red, Yellow, Blue, Green, White, Orange, Brown, Gray