



## XLPE Hook-Up Wire UL 10368 105°C 300V

Daburn Cross-Linked Polyethylene (XLPE) Wire exhibits the following characteristics:

- Low-Smoke Zero Halogen (LSZH)
- Excellent Mechanical Strength and Abrasion Resistance
- Very Good Electrical Insulating Properties
- Excellent Thermal Stability
- Highly Resistant to Chemicals and Solvents
- Excellent Resistance to Ozone and Oxidation
- Very Good Flexibility

This wire is ideally suited for lighting equipment, motor and coil leads, transformers, control panels, military equipment, industrial controls, computers, and appliance wiring applications. This wire meets UL Style 10368.

**Description:** Single conductor stranded tinned copper insulated with .010" XLPE insulation. This construction allows for a uniform, flexible, concentric, quality construction.

**Operating Temperature:** -40°C to +105°C

**Voltage Rating:** 300 Volts UL, 600 Volts Peak UL

FT2 Flame Rating.

This series is RoHS compliant.

Catalog Number	AWG	Strand	Nom. Wall		Nom. O.D.		Conductor Resistance 20°C Ohm/mft
			Inches	mm	Inches	mm	
2235/18	18	16/30	.010	0.25	.065	1.65	7.06
2235/20	20	21/33	.010	0.25	.057	1.45	11.2
2235/22	22	17/34	.010	0.25	.050	1.26	18.1
2235/24	24	11/34	.010	0.25	.043	1.10	28.7
2235/26	26	7/34	.010	0.25	.039	0.98	45.8
2235/28	28	7/36	.010	0.25	.035	0.88	72.8
2235/30	30	7/38	.010	0.25	.031	0.80	116.2

**Standard Put-Ups:** 100 feet, 500 feet, 1,000 feet

**Colors Available:** Black, Red, White, Green, Yellow, Blue, Brown, Grey, Violet, Orange