

#2354 Stainless Steel Expandable Braided Tubular Sleeving

- Made in the same manner as AA59569 (formerly QQB575) braid.
- Manufactured to provide shield coverage of 90% minimum (70% for .078" and smaller) at the nominal diameters specified.
- We stock Type 304 (non-magnetic) stainless steel. Type 430 (magnetic) stainless steel wire is available to order. Please call for quote for Type 430 stainless steel.
- Stainless Steel braids are ideal in corrosive or abrasive environments and high temperature applications.

Daburn Part Number	Nom. ID Rounded	Construction	Pounds per 1000 ft.	Indiv. Wire AWG	AWG Equivalent	Nominal CMA
2354-1/32	1/32"	16-3-36	4	36	19	1200
2354-1/16	1/16"	24-2-36	4	36	19	1200
2354-5/64	5/64"	24-3-36	6	36	18	1800
2354-7/64	7/64"	24-4-36	8	36	16	2400
2354-1/8	1/8"	24-5-36	10	36	15	3000
2354-5/32	5/32"	32-6-34	28	34	11	8000
2354-11/64	11/64"	24-7-36	14	36	14	4200
2354-3/16	3/16"	24-8-36	16	36	13	4800
2354-7/32	7/32"	24-10-36	20	36	12	6000
2354-1/4	1/4"	24-13-36	25	36	11	7800
2354-1/4A	1/4"	32-8-34	36	34	10	9800
2354-5/16	5/16"	32-8-32	55	32	9	14500
2354-3/8	3/8"	48-7-36	28	36	11	8400
2354-7/16	7/16"	48-8-36	35	36	10	9600
2354-1/2	1/2"	48-9-36	40	36	10	10800
2354-5/8	5/8"	48-11-36	47	36	9	13200
2354-3/4	3/4"	48-15-36	59	36	8	18000
2354-7/8	7/8"	48-18-36	72	36	7	21600
2354-1	1.0"	48-7-30	124	30	5	33600
2354-1 1/2	1 1/2"	48-10-30	144	30	3	48000