



Daburn #2416 – PFA High Temperature Wire UL Style 10362

Daburn PFA High Temperature Wire has the following characteristics:

- Very Good Mechanical Strength and Abrasion Resistance
- Excellent Electrical Insulating Properties
- Excellent Thermal Stability
- Resistant to Chemicals and Solvents
- Heat, Age, & Ozone Resistant
- Good Flexibility
- Thin Walls for Weight and Space Savings
- Good Lubricity (low coefficient of friction)

Suitable for use as internal wiring in appliances and electronic equipment. This wire meets UL Style 10362.

Description: Single conductor stranded nickel plated copper insulated with extruded PFA insulation.

Operating Temperature: -65°C to +250°C

Voltage Rating: 600 Volts UL

This series is RoHS compliant.

Catalog Number	AWG	Strand	Nom. Wall		Nom. O.D.	
			Inches	mm	Inches	mm
2416/14	14	19/27	.010	0.25	.089	2.26
2416/16	16	19/29	.010	0.25	.076	1.93
2416/18	18	19/30	.010	0.25	.064	1.63
2416/20	20	19/32	.010	0.25	.055	1.40
2416/22	22	7/30	.010	0.25	.050	1.27
2416/24	24	7/32	.010	0.25	.044	1.18

Colors Available: Black, Red, White, Green, Yellow, Blue, Brown, Grey, Violet, Orange
Tinned Plated & Silver plated copper conductors also available. Call to inquire.